UW9899 Mini Saddle

Profile specification · milled to this sheet · Rev A · 10/09/2026

A mini saddle: a solid, low-crowned threshold over the seam between two fastened-down floors of the same height.

DIMENSIONED SECTION · AS INSTALLED, FLOOR DOWN · ENLARGED ABOUT 2.6× · UNITS: INCHES



BOLD TEAL = HELD TO ±1/64" · GREY REF = REFERENCE SHAPE, THE SECTION GOVERNS

CORRECT THE RUN

The stocked sticks measure 0.279" high. Mill the next run to this sheet: 1/4" high.


SIZE	1-1/4" × 1/4" · 12' stock · sold by the linear foot
PART NUMBERS	Red Oak UW9899RO · White Oak UW9899WO · Hickory UW9899HK · Maple UW9899MP
HELD DIMENSIONS	Width 1-1/4", height 1/4" — ±1/64".
REFERENCE SHAPE	Everything marked REF is the scanned profile's own shape, re-scaled to the held sizes; the section governs.
GRADE	Select & Better — clear walking face. Character grade on request to match the floor.
MOISTURE	Kiln-dried and conditioned to 6–8% MC to match the flooring, checked before moulding.
GAUGE	Run to the UWP acrylic gauge for UW9899 — first article plus in-run QC every lot.

Full-Scale Template

UW9899 Mini Saddle · 1:1 · Rev A · 10/09/2026

PRINT AT 100%

Set the print dialog to Actual Size / 100% and turn off Fit to Page; the check bar must read exactly 3". Stand a cut end of the first article on the outline: it should cover it with no daylight at the drop or the top.





UW9899 · 1.250" × 0.250" · ACTUAL SIZE, FLOOR DOWN